



- * Delivers 10,000 hrs of reliable performance
- * Quality design exceeds IEC-252 Class B Industry Reliability Standards
- * Patented "Safe Failure System"
- * Manufactured in North America by Regal Beloit Corporation
- * Over 50+ years of manufacturing and engineering experience
- * -40°C to 70°C operating temperature

370 VAC - OVAL - MOTOR RUN CAPACITORS

FASCO MODEL	UF1	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
C3S2	2.0	370	AC	1.25	OVAL	1.56
C3S3	3.0	370	AC	1.25	OVAL	1.56
C3S4	4.0	370	AC	1.25	OVAL	1.56
C3S5	5.0	370	AC	1.25	OVAL	1.56
C3S6	6.0	370	AC	1.25	OVAL	2.12
C3S7.5	7.5	370	AC	1.25	OVAL	2.12
C3S10	10.0	370	AC	1.25	OVAL	2.88
C3S12.5	12.5	370	AC	1.25	OVAL	2.88
C3S15	15.0	370	AC	1.25	OVAL	2.88

FASCO MODEL	UF1	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
C3S17.5	17.5	370	AC	1.25	OVAL	3.88
C3S20	20.0	370	AC	1.25	OVAL	3.88
C3S25	25.0	370	AC	1.25	OVAL	3.88
C3S30	30.0	370	AC	1.25	OVAL	4.75
C3S35	35.0	370	AC	1.25	OVAL	4.75
C3S40	40.0	370	AC	1.75	OVAL	3.88
C3S45	45.0	370	AC	1.75	OVAL	3.88
C3S50	50.0	370	AC	1.75	OVAL	3.88
C3S60	60.0	370	AC	1.75	OVAL	4.75

440 VAC - OVAL - MOTOR RUN CAPACITORS

FASCO MODEL	UF1	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
C4S5	5.0	440	AC	1.25	OVAL	2.12
C4S7.5	7.5	440	AC	1.25	OVAL	2.88
C4S10	10.0	440	AC	1.25	OVAL	2.88
C4S12.5	12.5	440	AC	1.25	OVAL	3.88
C4S15	15.0	440	AC	1.25	OVAL	4.75
C4S17.5	17.5	440	AC	1.25	OVAL	4.75
C4S20	20.0	440	AC	1.25	OVAL	4.75

FASCO MODEL	UF1	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
C4S25	25.0	440	AC	1.25	OVAL	4.75
C4S30	30.0	440	AC	1.75	OVAL	3.88
C4S35	35.0	440	AC	1.75	OVAL	3.88
C4S40	40.0	440	AC	1.75	OVAL	3.88
C4S45	45.0	440	AC	1.75	OVAL	4.75
C4S50	50.0	440	AC	1.75	OVAL	4.75
C4S60	60.0	440	AC	2.00	OVAL	4.25

370 VAC - ROUND - MOTOR RUN CAPACITORS

FASCO MODEL	UF1	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
C3RS5	5.0	370	AC	1.75	ROUND	2.88
C3RS7.5	7.5	370	AC	1.75	ROUND	2.88
C3RS10	10.0	370	AC	1.75	ROUND	2.88
C3RS15	15.0	370	AC	1.75	ROUND	2.88
C3RS17.5	17.5	370	AC	1.75	ROUND	2.88
C3RS20	20.0	370	AC	1.75	ROUND	2.88
C3RS25	25.0	370	AC	1.75	ROUND	2.88
C3RS30	30.0	370	AC	1.75	ROUND	3.88

FASCO MODEL	UF1	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
C3RS35	35.0	370	AC	1.75	ROUND	3.88
C3RS40	40.0	370	AC	1.75	ROUND	3.88
C3RS45	45.0	370	AC	1.75	ROUND	4.75
C3RS50	50.0	370	AC	1.75	ROUND	4.75
C3RS55	55.0	370	AC	1.75	ROUND	4.75
C3RS60	60.0	370	AC	1.75	ROUND	4.75
C3RS70	70.0	370	AC	2.50	ROUND	4.75
C3RS80	80.0	370	AC	2.50	ROUND	4.75

440 VAC - ROUND - MOTOR RUN CAPACITORS

FASCO MODEL	UF1	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
C4RS5	5.0	440	AC	1.75	ROUND	2.88
C4RS7.5	7.5	440	AC	1.75	ROUND	2.88
C4RS10	10.0	440	AC	1.75	ROUND	2.88
C4RS12.5	12.5	440	AC	1.75	ROUND	2.88
C4RS15	15.0	440	AC	1.75	ROUND	2.88
C4RS20	20.0	440	AC	1.75	ROUND	2.88
C4RS25	25.0	440	AC	1.75	ROUND	3.88
C4RS30	30.0	440	AC	1.75	ROUND	3.88

FASCO MODEL	UF1	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
C4RS35	35.0	440	AC	2.00	ROUND	3.88
C4RS40	40.0	440	AC	1.75	ROUND	4.75
C4RS45	45.0	440	AC	2.00	ROUND	3.88
C4RS50	50.0	440	AC	2.00	ROUND	5.75
C4RS55	55.0	440	AC	2.50	ROUND	4.75
C4RS60	60.0	440	AC	2.50	ROUND	4.75
C4RS70	70.0	440	AC	2.50	ROUND	4.75
C4RS80	80.0	440	AC	2.50	ROUND	5.75

Thermally protected • UL recognized • CSA or ULc certified
NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.



370 VAC - DUAL - OVAL MOTOR RUN CAPACITORS

FASCO MODEL	UF1	UF2	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
▶ C3D1010	10.0	10.0	370	AC	1.75	OVAL	2.12
▶ C3D155	15.0	5.0	370	AC	1.75	OVAL	2.88
▶ C3D157.5	15.0	7.5	370	AC	1.75	OVAL	2.88
▶ C3D1510	15.0	10.0	370	AC	1.75	OVAL	2.88
▶ C3D205	20.0	5.0	370	AC	1.75	OVAL	2.88
▶ C3D207.5	20.0	7.5	370	AC	1.75	OVAL	2.88
▶ C3D2010	20.0	10.0	370	AC	1.75	OVAL	3.88
▶ C3D255	25.0	5.0	370	AC	1.75	OVAL	2.88
▶ C3D257.5	25.0	7.5	370	AC	1.75	OVAL	2.88
▶ C3D2510	25.0	10.0	370	AC	1.75	OVAL	2.88
▶ C3D305	30.0	5.0	370	AC	1.75	OVAL	3.88
▶ C3D307.5	30.0	7.5	370	AC	1.75	OVAL	3.88
▶ C3D3010	30.0	10.0	370	AC	1.75	OVAL	3.88

FASCO MODEL	UF1	UF2	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
▶ C3D355	35.0	5.0	370	AC	1.75	OVAL	3.88
▶ C3D357.5	35.0	7.5	370	AC	1.75	OVAL	3.88
▶ C3D3510	35.0	10.0	370	AC	1.75	OVAL	3.88
▶ C3D405	40.0	5.0	370	AC	1.75	OVAL	3.88
▶ C3D407.5	40.0	7.5	370	AC	1.75	OVAL	3.88
▶ C3D4010	40.0	10.0	370	AC	1.75	OVAL	3.88
▶ C3D455	45.0	5.0	370	AC	1.75	OVAL	3.88
▶ C3D457.5	45.0	7.5	370	AC	1.75	OVAL	3.88
▶ C3D4510	45.0	10.0	370	AC	1.75	OVAL	3.88
▶ C3D505	50.0	5.0	370	AC	1.75	OVAL	4.75
▶ C3D507.5	50.0	7.5	370	AC	1.75	OVAL	4.75
▶ C3D5010	50.0	10.0	370	AC	2.00	OVAL	4.75

440 VAC - DUAL - OVAL MOTOR RUN CAPACITORS

FASCO MODEL	UF1	UF2	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
▶ C4D1010	10.0	10.0	440	AC	1.75	OVAL	2.88
▶ C4D155	15.0	5.0	440	AC	1.75	OVAL	2.88
▶ C4D157.5	15.0	7.5	440	AC	1.75	OVAL	2.88
▶ C4D1510	15.0	10.0	440	AC	1.75	OVAL	3.88
▶ C4D205	20.0	5.0	440	AC	1.75	OVAL	2.88
▶ C4D207.5	20.0	7.5	440	AC	1.75	OVAL	3.88
▶ C4D2010	20.0	10.0	440	AC	1.75	OVAL	3.88
▶ C4D255	25.0	5.0	440	AC	1.75	OVAL	3.88
▶ C4D257.5	25.0	7.5	440	AC	1.75	OVAL	3.88
▶ C4D2510	25.0	10.0	440	AC	1.75	OVAL	4.75
▶ C4D305	30.0	5.0	440	AC	1.75	OVAL	3.88
▶ C4D307.5	30.0	7.5	440	AC	1.75	OVAL	3.88
▶ C4D3010	30.0	10.0	440	AC	1.75	OVAL	4.75

FASCO MODEL	UF1	UF2	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
▶ C4D355	35.0	5.0	440	AC	1.75	OVAL	4.75
▶ C4D357.5	35.0	7.5	440	AC	1.75	OVAL	4.75
▶ C4D3510	35.0	10.0	440	AC	1.75	OVAL	4.75
▶ C4D405	40.0	5.0	440	AC	1.75	OVAL	4.75
▶ C4D407.5	40.0	7.5	440	AC	1.75	OVAL	4.75
▶ C4D4010	40.0	10.0	440	AC	2.00	OVAL	4.75
▶ C4D455	45.0	5.0	440	AC	1.75	OVAL	4.75
▶ C4D4510	45.0	10.0	440	AC	1.75	OVAL	4.75
▶ C4D457.5	45.0	7.5	440	AC	2.00	OVAL	4.75
▶ C4D505	50.0	5.0	440	AC	2.00	OVAL	5.25
▶ C4D507.5	50.0	7.5	440	AC	2.00	OVAL	5.25
▶ C4D5010	50.0	10.0	440	AC	2.00	OVAL	5.25

370 VAC - DUAL - ROUND MOTOR RUN CAPACITORS

FASCO MODEL	UF1	UF2	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
▶ C3DR155	15.0	5.0	370	AC	2.00	ROUND	2.88
▶ C3DR157.5	15.0	7.5	370	AC	2.00	ROUND	2.88
▶ C3DR1510	15.0	10.0	370	AC	2.00	ROUND	2.88
▶ C3DR205	20.0	5.0	370	AC	2.00	ROUND	2.88
▶ C3DR207.5	20.0	7.5	370	AC	2.00	ROUND	2.88
▶ C3DR2010	20.0	10.0	370	AC	2.00	ROUND	2.88
▶ C3DR255	25.0	5.0	370	AC	2.00	ROUND	2.88
▶ C3DR257.5	25.0	7.5	370	AC	2.00	ROUND	2.88
▶ C3DR2510	25.0	10.0	370	AC	2.00	ROUND	2.88
▶ C3DR305	30.0	5.0	370	AC	2.00	ROUND	2.88
▶ C3DR307.5	30.0	7.5	370	AC	2.00	ROUND	3.88
▶ C3DR3010	30.0	10.0	370	AC	2.00	ROUND	3.88
▶ C3DR355	35.0	5.0	370	AC	2.00	ROUND	3.88
▶ C3DR357.5	35.0	7.5	370	AC	2.00	ROUND	3.88
▶ C3DR3510	35.0	10.0	370	AC	2.00	ROUND	3.88
▶ C3DR405	40.0	5.0	370	AC	2.00	ROUND	3.88
▶ C3DR407.5	40.0	7.5	370	AC	2.00	ROUND	3.88
▶ C3DR4010	40.0	10.0	370	AC	2.00	ROUND	3.88

FASCO MODEL	UF1	UF2	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
▶ C3DR455	45.0	5.0	370	AC	2.00	ROUND	3.88
▶ C3DR457.5	45.0	7.5	370	AC	2.00	ROUND	3.88
▶ C3DR4510	45.0	10.0	370	AC	2.00	ROUND	4.75
▶ C3DR505	50.0	5.0	370	AC	2.00	ROUND	3.88
▶ C3DR507.5	50.0	7.5	370	AC	2.00	ROUND	4.75
▶ C3DR5010	50.0	10.0	370	AC	2.00	ROUND	4.75
▶ C3DR555	55.0	5.0	370	AC	2.50	ROUND	3.88
▶ C3DR557.5	55.0	7.5	370	AC	2.50	ROUND	3.88
▶ C3DR5510	55.0	10.0	370	AC	2.50	ROUND	3.88
▶ C3DR605	60.0	5.0	370	AC	2.50	ROUND	3.88
▶ C3DR607.5	60.0	7.5	370	AC	2.50	ROUND	4.75
▶ C3DR6010	60.0	10.0	370	AC	2.50	ROUND	4.75
▶ C3DR705	70.0	5.0	370	AC	2.50	ROUND	4.75
▶ C3DR707.5	70.0	7.5	370	AC	2.50	ROUND	4.75
▶ C3DR7010	70.0	10.0	370	AC	2.50	ROUND	4.75
▶ C3DR805	80.0	5.0	370	AC	2.50	ROUND	4.75
▶ C3DR807.5	80.0	7.5	370	AC	2.50	ROUND	4.75
▶ C3DR8010	80.0	10.0	370	AC	2.50	ROUND	4.75





440 VAC - DUAL - ROUND MOTOR RUN CAPACITORS

FASCO MODEL	UF1	UF2	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
▶ C4DR155	15.0	5.0	440	AC	2.00	ROUND	2.88
▶ C4DR157.5	15.0	7.5	440	AC	2.00	ROUND	3.88
▶ C4DR1510	15.0	10.0	440	AC	2.00	ROUND	3.88
▶ C4DR205	20.0	5.0	440	AC	2.00	ROUND	2.88
▶ C4DR207.5	20.0	7.5	440	AC	2.00	ROUND	3.88
▶ C4DR2010	20.0	10.0	440	AC	2.00	ROUND	3.88
▶ C4DR255	25.0	5.0	440	AC	2.00	ROUND	3.88
▶ C4DR257.5	25.0	7.5	440	AC	2.00	ROUND	3.88
▶ C4DR2510	25.0	10.0	440	AC	2.00	ROUND	3.88
▶ C4DR305	30.0	5.0	440	AC	2.00	ROUND	3.88
▶ C4DR307.5	30.0	7.5	440	AC	2.00	ROUND	3.88
▶ C4DR3010	30.0	10.0	440	AC	2.00	ROUND	3.88
▶ C4DR355	35.0	5.0	440	AC	2.00	ROUND	4.75
▶ C4DR357.5	35.0	7.5	440	AC	2.00	ROUND	4.75
▶ C4DR3510	35.0	10.0	440	AC	2.50	ROUND	3.88
▶ C4DR405	40.0	5.0	440	AC	2.50	ROUND	2.88
▶ C4DR407.5	40.0	7.5	440	AC	2.00	ROUND	4.75
▶ C4DR4010	40.0	10.0	440	AC	2.00	ROUND	4.75

FASCO MODEL	UF1	UF2	VOLTS		BASE SIZE	CAN TYPE	CASE HEIGHT
▶ C4DR455	45.0	5.0	440	AC	2.50	ROUND	3.88
▶ C4DR457.5	45.0	7.5	440	AC	2.50	ROUND	3.88
▶ C4DR4510	45.0	10.0	440	AC	2.50	ROUND	3.88
▶ C4DR505	50.0	5.0	440	AC	2.50	ROUND	4.25
▶ C4DR507.5	50.0	7.5	440	AC	2.50	ROUND	4.75
▶ C4DR5010	50.0	10.0	440	AC	2.50	ROUND	4.75
▶ C4DR555	55.0	5.0	440	AC	2.50	ROUND	4.75
▶ C4DR557.5	55.0	7.5	440	AC	2.50	ROUND	4.75
▶ C4DR5510	55.0	10.0	440	AC	2.50	ROUND	4.75
▶ C4DR605	60.0	5.0	440	AC	2.50	ROUND	4.75
▶ C4DR607.5	60.0	7.5	440	AC	2.50	ROUND	4.75
▶ C4DR6010	60.0	10.0	440	AC	2.50	ROUND	4.75
▶ C4DR705	70.0	5.0	440	AC	2.50	ROUND	5.25
▶ C4DR707.5	70.0	7.5	440	AC	2.50	ROUND	4.75
▶ C4DR7010	70.0	10.0	440	AC	2.50	ROUND	4.75
▶ C4DR805	80.0	5.0	440	AC	2.50	ROUND	4.75
▶ C4DR807.5	80.0	7.5	440	AC	2.50	ROUND	4.75
▶ C4DR8010	80.0	10.0	440	AC	2.50	ROUND	4.75

LIFE-LINE™ CAPACITOR KIT REPLACEMENT PARTS

Life-Line™



FEATURES

The Life-Line™ Capacitor Kit is the all in one replacement kit for your single and dual run capacitor needs.

- IEC-252 Class B Industry Reliability Standards
- UL Listed
- Convenient carrying case to keep you organized
- PROLINE™ Capacitors with over 10,000 Hrs of Reliable Performance

BENEFITS

- Save time and money by having exactly what you need on the job and ability to only use and replace what you need.
- This kit has been designed to cover over 85% of the most commonly used capacitor ratings in the field today.
- Turn six capacitors into 48 duals with no guess work using the UL approved (patent-pending Life-Line™ Device).

LCKP-001

Life-Line™ Capacitor Kit

INCLUDED in KIT:

- * 6 Best in Class Motor Run Capacitors
- * 2 Life-Line™ devices
- * 1 Capacitor Mounting Hardware Kit
- * 1 Device Mounting Hardware Kit
- * 1 Robust Carrying Case
- * Installation Guide



LCK-CID-001

Life-Line™ Device (4 pack)



LCK-SBA-001

Capacitor Mounting Hardware Kit
 * 3 adjustable brackets
 * Self tapping mounting screws



LCK-DBA-001

Device Mounting Hardware Kit
 * 3 different sizes for oval & round

Thermally protected • UL recognized • CSA or ULc certified

NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.