

BLOWER WHEEL

Single Inlet


FASCO

SINGLE INLET						
PART NUMBER	DIA-METER	WIDTH	ROTA-TION	BORE	MAX RPM	STD PACK
1-6123	4	7/8	C.W.	5/16	3600	4
1-6038	3	1 7/8	C.W.	1/4	5000	4
1-6039	3	1 7/8	C.C.W.	1/4	5000	4
1-6040	3 13/16	1 7/8	C.C.W.	1/4	5000	4
1-6041	3 13/16	1 7/8	C.W.	1/4	5000	4
1-6042	3 13/16	1 7/8	C.C.W.	5/16	5000	4
1-6043	3 13/16	1 7/8	C.W.	5/16	5000	4
1-6044	3 13/16	2 1/2	C.W.	5/16	5000	4
1-6045	3 13/16	2 1/2	C.C.W.	5/16	5000	4
1-6114	3 27/32	1 1/4	C.W.	1/4	5600	4
1-6113	3 27/32	1	C.W.	1/4	5800	4
1-6051	3 27/32	1 13/64	C.C.W.	1/4	5640	4
1-6141	4	1 1/2	C.C.W.	5/16	3600	4
1-6133	4	2 1/2	C.C.W.	1/4	3600	3
1-6046	4 1/4	2	C.C.W.	1/4	4500	4
1-6047	4 1/4	2	C.C.W.	5/16	4500	4
1-6052	4 1/4	2 15/16	C.C.W.	1/4	4500	3
1-6160	4 17/32	1 1/4	C.W.	5/16	6300	4
1-6161	4 17/32	1 1/4	C.C.W.	5/16	6300	4
1-6048	4 23/32	2 15/16	C.W.	5/16	3600	3
1-6000	4 23/32	2 15/16	C.C.W.	5/16	3600	3
1-6024	5 13/64	2 1/2	C.W.	5/16	3600	4
1-6025	5 13/64	2 1/2	C.C.W.	5/16	3600	4
1-6053	5 13/64	2 29/32	C.W.	5/16	3600	3
1-6054	5 13/64	2 29/32	C.C.W.	5/16	3600	3
1-6143	5 3/4	1 1/2	C.C.W.	5/16	3600	4
1-6026	5 45/64	2 15/16	C.C.W.	5/16	3000	3
1-6002	5 45/64	4	C.W.	1/2	2800	2
1-6057	5 45/64	4	C.C.W.	1/2	2800	2
1-6058	6	3 1/4	C.W.	1/2	2400	3
1-6010	6	3 1/4	C.C.W.	1/2	2400	3
1-6060	6 3/16	2 15/16	C.C.W.	3/8	3000	3

SINGLE INLET						
PART NUMBER	DIA-METER	WIDTH	ROTA-TION	BORE	MAX RPM	STD PACK
1-6063	6 25/64	4	C.W.	1/2	1700	2
1-6064	6 25/64	4	C.C.W.	1/2	1700	2
1-6066	7 1/8	2	C.C.W.	5/16	2900	4
1-6005	7 1/8	4	C.C.W.	1/2	1500	2
1-6070	7 31/64	3 1/2	C.W.	1/2	1800	3
1-6071	7 31/64	3 1/2	C.C.W.	1/2	1800	3
1-6006	8 5/64	4	C.W.	1/2	1650	3
1-6074	8 5/64	4	C.C.W.	1/2	1650	3
1-6077	8 35/64	3	C.C.W.	1/2	2050	4
1-6076	8 35/64	3	C.W.	1/2	2050	4
1-6007	9 1/8	4 1/4	C.W.	1/2	1475	3
1-6078	9 1/8	4 1/4	C.C.W.	1/2	1475	3
1-6008	9 1/8	5	C.W.	1/2	1350	2
1-6009	9 1/8	5	C.C.W.	1/2	1350	2
1-6079	9 31/32	4	C.W.	1/2	1350	3
1-6080	9 31/32	4	C.C.W.	1/2	1350	3
1-6027	9 31/32	6	C.W.	1/2	1100	2
1-6028	9 31/32	6	C.C.W.	1/2	1100	2

TYPICAL APPLICATIONS


- Condensers
- Small appliances
- Furnaces
- Draft booster
- Flue exhaust
- Galvanized steel



Rotation viewed side opposite hub.

TYPICAL APPLICATIONS

- Condensers
- Small appliances
- Furnaces
- Galvanized steel except 2-6033 and 2-6034 are aluminum



Rotation viewed hub side.

DOUBLE INLET						
PART NUMBER	DIA-METER	WIDTH	ROTA-TION	BORE	MAX RPM	STD PACK
2-6011	4 ²⁷ / ₃₂	7	C.W.	1/2	3600	1
2-6029	4 ²⁷ / ₃₂	7	C.C.W.	1/2	3600	1
2-6082	5 ¹³ / ₃₂	6 ⁵⁵ / ₆₄	C.C.W.	3/8	3600	1
2-6030	5 ¹ / ₄	6 ⁷ / ₈	C.W.	1/2	3600	1
2-6012	5 ¹⁹ / ₆₄	7	C.C.W.	1/2	3600	1
2-6013	5 ⁹ / ₁₆	6 ¹ / ₂	C.W.	1/2	2500	1
2-6014	5 ⁹ / ₁₆	6 ¹ / ₂	C.C.W.	1/2	2500	1
2-6031	5 ⁴⁵ / ₆₄	7 ⁵ / ₈	C.W.	1/2	3000	1
2-6032	5 ⁴⁵ / ₆₄	7 ⁵ / ₈	C.C.W.	1/2	3000	1
2-6033	5 ³ / ₄	7 ⁵⁵ / ₆₄	C.W.	1/2	1700	1
2-6083	6 ²⁵ / ₆₄	7	C.W.	1/2	2050	1
2-6015	6 ²⁵ / ₆₄	7	C.C.W.	1/2	2050	1
2-6084	6 ³ / ₁₆	7 ⁵ / ₈	C.W.	1/2	3000	1
2-6085	6 ³ / ₁₆	7 ⁵ / ₈	C.C.W.	1/2	3000	1
2-6034	6 ²⁵ / ₆₄	8	C.W.	1/2	1500	1
2-6139	6 ²⁵ / ₆₄	6 ¹ / ₄	C.C.W.	3/4	2275	1
2-6086	7 ³¹ / ₆₄	4	C.W.	3/4	2700	2
2-6087	7 ³¹ / ₆₄	4	C.C.W.	3/4	2700	2
2-6035	7 ³¹ / ₆₄	4 ¹ / ₂	C.W.	3/4	2400	2
2-6036	7 ³¹ / ₆₄	4 ¹ / ₂	C.C.W.	3/4	2400	2
2-6016	7 ³¹ / ₆₄	6	C.W.	3/4	1950	2
2-6017	7 ³¹ / ₆₄	6	C.C.W.	3/4	1950	2
2-6018	7 ³¹ / ₆₄	9	C.W.	1/2	1600	1
2-6089	9 ¹ / ₂	6	C.W.	1/2	1750	2
2-6019	9 ¹ / ₂	7	C.W.	1/2	1550	1
2-6090	9 ¹ / ₂	8	C.W.	1/2	1400	1
2-6020	9 ¹ / ₂	9 ¹ / ₄	C.W.	1/2	1300	1
2-6092	10 ²⁵ / ₃₂	6	C.W.	1/2	1550	2
2-6093	10 ²⁵ / ₃₂	7	C.W.	1/2	1350	2
2-6021	10 ²⁵ / ₃₂	7 ³ / ₄	C.W.	1/2	1250	1
2-6037	10 ²⁵ / ₃₂	9 ¹ / ₄	C.W.	1/2	1200	1
2-6022	10 ²⁵ / ₃₂	10 ¹ / ₂	C.W.	1/2	1150	1